

DECLARATION OF CONFORMITY

I hereby declare that the product

Description: SMART PHONE

Type or model name: SF 01

Brand name: BLAUPUNKT

(Name of product, type or model, batch or serial number)

Hardware version number:	4032_MB_V2.0
Software version number:	Blaupunkt_Telenor_Hu_V03
Adapter:	Model: SF 01 Brand: BLAUPUNKT Power supply and ADP(rating): Input: AC 100V-240V, 50/60Hz 200mA Output: DC 5V, 750mA
Battery:	Model: SF 01 Brand: N/A Battery(rating): Rated Voltage: 3.7V Charge Limit: 4.2V Capacity :1400mAh
USB line	Model: SF 01 Brand: BLAUPUNKT Length:100cm
Earphone	Model: SF 01 Brand: BLAUPUNKT Length:110cm
Dipole Antenna(Earphone acts as FM antenna which becomes an integral antenna):	Model: SF 01 Brand: BLAUPUNKT

satisfies all the technical regulations applicable to the product within the scope of Council Directives 2014/53/EU:

All essential radio test suites have been carried out.

EN 60950-1:2006 + A11:2009 + A1:2010 + A12: 2011 + A2: 2013

Draft ETSI EN 301 489-01 V2.2.0(2017-03)

Draft ETSI EN 301 489-17 V3.2.0(2017-03)

Draft ETSI EN 301 489-52 V1.1.0(2016-11)

Draft ETSI EN 301 489-19 V2.1.0(2017-03)

EN 55032:2015

EN 55035:2017

EN 61000-3-2:2014

EN 61000-3-3:2013

ETSI EN 301 908-1 V11.1.1 (2016-07)

ETSI EN 301 908-2 V11.1.2 (2017-08)

ETSI EN 301 511 V12.5.1(2017-03)

ETSI EN 300 328 V2.1.1(2016-11)

ETSI EN 303 413 V1.1.1(2017-06)

Final draft ETSI EN 303 345 V1.1.1(2017-03)

EN 50663: 2017

EN 62209-1: 2016; EN 62209-2: 2010;

EN 50360: 2017; EN 50566: 2017

Feature:

GSM

Frequency Bands:

GSM 900: 880 ~ 915 MHz(TX) 925 ~ 960 MHz (RX)

GSM 1800: 1710 ~ 1785 MHz(TX) 1805 ~ 1880 MHz(RX)

Modulation Mode: GMSK for GPRS, GMSK and 8PSK for EDGE

Antenna Type: PIFA

Antenna Gain: GSM 900: -3.9dBi GSM 1800: -3.9dBi

Max power:33.10dBm

WCDMA

Frequency Bands:

WCDMA2100: 1920 ~ 1980 MHz(TX) 2110 ~ 2170 MHz(Rx)

WCDMA900: 880 ~ 915 MHz(TX) 925 ~ 960 MHz(Rx)

Modulation Mode: WCDMA: QPSK;HSDPA:QPSK/16QAM; HSUPA:BPSK;

Antenna Type: PIFA

Antenna Gain: WCDMA 2100:-3.9dBi WCDMA 900:-3.9dBi

Max power:22.51dBm

Bluetooth 4.0

Frequency Bands:2402-2480 MHz

Modulation Mode: GFSK(1Mbps)

Antenna Type: PIFA

Antenna Gain:-3.9dBi

EIRP Max power:-3.87dBm

2.4G WIFI

Frequency Bands:

IEEE 802.11b /g /n(20MHz):2412-2472 MHz

IEEE 802.11n(40MHz):2422-2462MHz

Modulation Mode: CCK/OFDM/DBPSK/DAPSK

Antenna Type: PIFA

Antenna Gain: -3.9dBi

EIRP Max power:16.72dBm

GPS

Frequency Bands:1.57542GHz

Modulation Mode: GSMK

Antenna Type: PIFA

Antenna Gain: -3.9dBi

FM

Frequency Bands:87.5-108MHz

Modulation Mode:FM

Antenna Type: Dipole Antenna

(Earphone acts as FM antenna which becomes an integral antenna)

Antenna Gain:-0.5dBi

NOTIFIED BODY: PHOENIX TEST-LAB GmbH

– **Address:**

Köningswinkel 10

D-32825 Blomberg

Germany

Identification Number: 0700

MANUFACTURER or AUTHORISED REPRESENTATIVE:

– **Address:**

HTM Mobile Kft.

1118 Budapest, Dayka Gábor utca 3. HUNGARY

This declaration is issued under the sole responsibility of the manufacturer and, if applicable, his authorised representative.

Point of contact:

2019-4-25

(Signature)

Name (in block letter)

Title (in block letter)

Company Name

Address

Tel / Fax

Email

Lois Wang

Account Manager

ZECHIN COMMUNICATION(HK) LIMITED

Unit 804, 8th Floor Desay Tech Building Gaoxin Road South,
Nanshan District, Shenzhen, China

+ 86 13510560658

lois@hkzechin.com

